



2300 Series

2306A-E14TAG2

Diesel Engine – Electropak

344 kWm at 1500 rpm
377 kWm at 1800 rpm



Economic Power

- Mechanically operated unit fuel injectors with advanced electronic control, combined with carefully matched turbocharging, give excellent fuel atomisation which leads to exceptional low fuel consumption.

Reliable Power

- Developed and tested using the latest engineering techniques and finite element analysis for high reliability.
- Low oil usage and low wear rates.
- High compression ratio ensures clean rapid starting in all conditions.
- Support comes from a worldwide network of 4,000 distributors and dealers.

Compact, Clean and Efficient Power

- Exceptional power to weight ratio and compact size gives optimum power density for ease of installation and more cost effective transportation.
- Designed to provide excellent service access for ease of maintenance.

The Perkins 2300 Series is a family of well-proven 6 cylinder in-line diesel engines. It is designed to address today's uncompromising demands within the power generation industry with particular focus on the standby market sector. Developed from a proven heavy-duty industrial base, the engine offers superior performance and reliability.

The 2306A-E14TAG2 is a turbocharged and air-to-air charge-cooled 6-cylinder diesel engine. It gives economic and durable operation for standby duty, low gaseous emissions, and high levels of performance and reliability.

This engine does not comply with harmonized international regulated emissions limits.

Engine Speed (rev/min)	Type of Operation	Typical Generator Output (Net)		Engine Power			
		kVA	kWe	Gross		Net	
				kWm	bhp	kWm	bhp
1500	Baseload Power	275	220	248	333	239	321
	Prime Power	350	280	313	420	304	408
	Standby Power	400	320	353	473	344	461
1800	Baseload Power	313	250	289	388	272	365
	Prime Power	400	320	365	489	348	466
	Standby Power	438	350	394	528	377	505

The above ratings represent the engine performance capabilities to conditions specified in ISO 8528/1, ISO 3046/1:1986, BS 5514/1. Derating may be required for conditions outside these; consult Perkins Engines Company Limited.

Generator powers are typical and are based on an average alternator efficiency and a power factor (cos. θ) of 0.8.

Fuel specification: BS 2869: Part 2 1998 Class A2 or ASTM D975 D2.

Lubricating oil: 15W40 to API CG4.

Rating Definitions

Baseload Power: Power available for continuous full load operation. Overload of 10% permitted for 1 hour in every 12 hours operation

Prime Power: Power available at variable load with a load factor not exceeding 80% of the prime power rating. Overload of 10% is permitted for 1 hour in every 12 hours operation

Standby Power: Power available in the event of a main power network failure up to a maximum of 500 hours per year of which up to 300 hours may be run continuously. Load factor may be up to 100% of standby power. No overload is permitted.

2300 Series

2306A-E14TAG2

Standard ElectropaK Specification

Air inlet

- Mounted air filter

Fuel system

- Mechanically actuated electronically controlled unit fuel injectors with full authority electronic control
- Governing to ISO 8528-5 class G3 with isochronous capability
- Replaceable 'ecoplus' fuel filter elements with primary filter/water separator
- Fuel Cooler

Lubrication system

- Wet sump with filler and dipstick
- Full-flow replaceable 'ecoplus' filter
- Oil cooler integral with filter header

Cooling system

- Gear-driven circulating pump
- Mounted belt-driven pusher fan
- Radiator supplied loose incorporating air-to-air charge cooler
- System designed for ambients up to 50°C

Electrical equipment

- 24 volt starter motor and 24 volt 70 amp alternator with DC output
- ECM mounted on engine with wiring looms and sensors
- 3 level engine protection system

Flywheel and housing

- High inertia flywheel to SAE J620 Size 14
- SAE ½ flywheel housing

Mountings


- Front engine mounting bracket

Literature

- User's Handbook and Parts Manual

Optional Equipment

- 110 volt/240 volt immersion heater
- Additional speed sensor
- Temperature and pressure sensors for gauges
- Electric hours counter
- Air filter rain hood
- Twin starters/facility for second starter
- Tool kit
- Additional manuals



Engine Speed	Fuel Consumption			
	1500 rev/min		1800 rev/min	
	g/kWh	l/hr	g/kWh	l/hr
Standby	196	78	209	91
Prime power	197	70	211	85
Baseload power	204	57	222	70
75% of prime power	212	56	219	66
50% of prime power	232	41	232	47

General Data

Number of cylinders	6
Cylinder arrangement	Vertical in-line
Cycle	4 stroke
Induction system	Turbocharged and air-to-air charge cooled
Combustion system	Direct injection
Cooling system	Water-cooled
Bore and stroke	137 x 165 mm
Displacement	14.6 litres
Compression ratio	15.9:1
Direction of rotation	Anti-clockwise, viewed on flywheel
Total lubrication system capacity	68 litres
Total coolant capacity	47 litres
Total dry weight	1690 kg
Dimensions	Length 2422 mm Width 1107 mm Height 1614 mm

Final weight and dimensions will depend on completed specification



Perkins Engines Company Limited

Peterborough PE1 5NA
United Kingdom
Telephone +44 (0)1733 583000
Fax +44 (0)1733 582240
www.perkins.com

Distributed by